



DECKING RISER PEDESTALS



DESCRIPTION

Adjustable support in height from 20 to 230 mm made of recycled polypropylene.



APPLICATIONS

- Used in the creation of flat roofs to support the joists and protect the waterproofing.

KEY FEATURES

- Precise height adjustment using the rotating nut : no additional tools required.
- Reinforcing ribs for higher compressive strength.
- Flange with chamfered edge to ensure a perfect support. All sections have drainage holes to prevent water retention.
- High resistance to crushing loads > 1 T.

PURPOSE

- Flat roofs accessible to pedestrians.
- Roof gardens.



DECKING RISER PEDESTALS

PACKING

Reference	20/30 mm	40/60 mm	50/80 mm	80/140 mm	140/230 mm
Packing	Bag of 40 parts	Bag of 60 parts	Bag of 60 parts	Bag of 40 parts	Bag of 40 parts
Per pallet	20 bags	16 bags	12 bags	14 bags	8 bags

TECHNICAL DETAILS

- **Material** : recycled polypropylene.
- **Colour** : black.
- **Vertical flange - height** : 25 mm.
- **Diameter flange** : 208 mm.
Bearing contact area > 300 cm².
- **Diameter head of the riser** : 120 mm.
Bearing contact area > 100 cm².

References	Weight
20/30 mm	158 g
40/60 mm	226 g
50/80 mm	248 g
80/140 mm	322 g
140/230 mm	500 g



RESISTANCE

- Resistant to extreme temperatures from -30°C to +60°C.
- UV and frost resistant.
- High resistance to crushing loads > 1 T.

HEIGHT



RECOMMENDATIONS

- Allow for an average of four support pedestals per square metre.

ENVIRONMENT

- This product meets hygiene, health and environmental requirements. It does not contain any hazardous components.