

# PAVING RISER PEDESTALS



## DESCRIPTION

Adjustable support in height from 20 to 230 mm made of recycled polypropylene.



## APPLICATIONS

- Used in the creation of flat roofs to support the slabs and protect the waterproofing.

## KEY FEATURES

- Precise height adjustment using the rotating nut : no additional tools required.
- Reinforcing ribs for higher compressive strength.
- Flange with chamfered edge to ensure a perfect support. All sections have drainage holes to prevent water retention.
- Divisible spacers.
- High resistance to crushing loads > 1 T.

## DESTINATION

- Flat roofs accessible to pedestrians.
- Roof gardens..



# PAVING RISER PEDESTALS

## PACKING

<b>Reference</b>	20/30 mm	40/60 mm	50/80 mm	80/140 mm	140/230 mm
<b>Packing</b>	Bag of 40 parts	Bag of 60 parts	Bag of 60 parts	Bag of 40 parts	Bag of 40 parts
<b>Per pallet</b>	20 bags	16 bags	12 bags	14 bags	8 bags

## TECHNICAL DETAILS

- **Material** : recycled polypropylene.
- **Colour** : black.
- **Spacers** : height : 9 mm / Thickness : 3 mm / Quantity : 4.
- **Diameter flange** : 208 mm.  
*Bearing contact area > 300 cm<sup>2</sup>*
- **Diameter head of the riser** : 120 mm.  
*Bearing contact area > 100 cm<sup>2</sup>*

References	Weight
20/30 mm	156 g
40/60 mm	223 g
50/80 mm	246 g
80/140 mm	321 g
140/230 mm	504 g



## RESISTANCE

- Resistant to extreme temperatures from -30°C to +60°C.
- UV and frost resistant.
- High resistance to crushing loads > 1 T.

## HEIGHT



From 20 to 30 mm



From 40 to 60 mm



From 50 to 80 mm



From 80 to 140 mm



From 140 to 230 mm

## RECOMMENDATIONS

- The paving used must self-supporting.
- Allow for an average of seven support pedestals per square metre for 40 cm x 40 cm tiles and five support pedestals per square metre for 50 cm x 50 cm tiles.

## ENVIRONMENT

- This product meets hygiene, health and environmental requirements. It does not contain any hazardous components.